HIGHLY STRENGHTENED GEAR

Patent number:

JP2138554

Publication date:

1990-05-28

Inventor:
Applicant:

FUSHIMI SHINJI; others: 04
NISSAN MOTOR CO LTD

Classification:

- international:

F16H55/06

- european:

Application number:


JP19880290861 19881116

Priority number(s):

Abstract of JP2138554

PURPOSE:To make a gear excellent in quality and high in strength by controlling the depth of an effective hardened layers of a root circle section and root circle corner radius section to be less than the specified percent of the effective hardened layer of a tooth surface on a pitch circle in the gear which is sintered or processed by nitride sintering.

CONSTITUTION: After a raw material for a gear has been processed by normal gas sintering or nitric sintering, for example, in a state that the material is in a round bar form, tooth forging is processed so as to let it be a gear raw material when it is hot or warm while remaining heat is being utilized, then, it is immersed in a neutral salt bath which is maintained at a hardening temperature (for example, 840 deg.C) so that it is hardened in oil (for example, 80 deg.C) thereafter. In this case, the depth of an effective hardened layers of a root circle section and a root circle corner radius section is controlled to be less than eighty percent of the depth of an effective hardened layer of a tooth surface on a pitch circle by a step of changing both the depth of the layer of sintering or niride sintering of the raw material in a round bar form and a working rate at the time of tooth forging. By this constitution, a highly strengthened gear of high quality can thereby be obtained, the tooth surface of which is free of the occurrence of depression and pitching and/or spalling owing to surface fatigue.



Also published as:

EP0371340 (A1) EP0371340 (B1)

Data supplied from the esp@cenet database - Patent Abstracts of Japan